



## Air separator ... of stainless steel **UB-450**

The Air Separator can be delivered in various versions depending on the customer's needs. The Air Separator housing can easily be mounted or moved to fit either the left or the right side of the conveyor. The Air Separator is built out of stainless steel and is delivered with control box ready to be connected to 3 phase electricity. The control box is delivered with variable speed control for airflow and belt.

- Durable 7,5 hp blower motor (adjustable speed).
- Easy access cleaning.
- Pneumatic controlled cylinder for lifting hood.
- Fan and motor swing out for cleaning.
- Removable poly sides for easy cleaning.
- All bearings are plastic housing with high quality stainless steel roller cartridges.
- Self levelling adjustable legs.

### Technical details:

Motor: Electric.  
Material: Stainless steel. Aisi 304.  
Finish: Glassblasted.

### Connections:

Power: 3 x 400-600 v  
50-60 hz, 7 kw, 14,5a.

### Consumption:

Power: 7 kw.  
Water: 4 bar, ca 30l/h.

**Capacity:** 850-1000 kg/h.

**Cleaning:** 6 bar.



Hafnargata 21  
240 Grindavik  
Iceland

Tel: +354 426 7950  
+354 426 7945  
Fax: +354 426 7940  
martak@vortex.is